



ANIMAL HUSBANDRY MACHINERY AND EQUIPMENT

Milking System



**Rapid Exit
Herringbone Milking Parlor**

Technical Details

All demountable hot dip galvanized rapid exit herringbone parlor stalls
Double zig-zag pipes at each side to direct the cows for standing 30° to the pit
Support posts at every stall with back plate
Pneumatic entry gate, 50x700 mm cylinders
Pneumatic swing up exit gates, 100x600 mm cylinders
Telescopically adjustable chess bar
Hotdip galvanized kerb with 1/2" pipe on top edge, stainless steel sliding hose holders
100x80 mm profile connectio between main support posts
120x80 mm main support posts
All construciton installation by cast and steel clamps, no welding required during installation
Two operator ladders
Benefit: Milker can see four teats of each milking cow during cluster attachment



Milking System



**Rapid Exit
Parallel Milking Parlor**

Technical Details

All demountable hot dip galvanized rapid exit parallel parlor stalls
Stainless steel backpan with slurry chanel and automatic flushing at every exit
Index gates, with out spring- problem free
Pneumatic entry gate, 50x900 mm cylinders
Pneumatic swing up exit gates with tandem cylinders for easy load and push back cows for milking
Tandem exit gate cylinders 125x375+75 mm
In concrete, durable stainless steel kerb with 1/2" pipe on top edge, stainless steel sliding hose holders
100x80 mm profile connectio between main support posts
120x80 mm in concrete main support posts
Three pool style stainless steel operator ladders.
Optional stainless steel cabinet