

Smart Fertilizer Agritech

WITH THE NEW GENERATION, HIGH-TECH SENSORS AND ELECTRONIC EQUIPMENT, YOU CAN INSTANTLY MONITOR THE DETAILED DATA READ THROUGH THE SMART FERTILIZER SPREADER VIA THE TOUCH USER SCREEN, TRACK THE FERTILIZED AREAS WITH MAPPING AND EASILY CONTROL THE MACHINE.

The amount of fertilizer applied per decare is automatically adjusted precisely with software control with respect to the vehicle speed calculated by the satellite signal. The spreading process is automatically started and stopped at the beginning and at the end of the rows to avoid overlapping fertilization. The amount of fertilizer per decare is calculated instantly with the load cells on the system and automatically calibrated by the software. Thanks to the sensors on the system, the amount of fertilizer in the tank can be monitored via the user screen.



Auto Start/Stop at Headlands

Automatic Fertilizer Amount Adjustment

Avoid Overlapping Fertilization

Tank Level Control

CENTER OFFICE

Kazım Dirik Mah. 296/2. No:33 Bornova,
İzmir/Türkiye
T: +90 232 700 22 94

info@narasmakina.com

EXHIBITION AND STORAGE CENTER

Fevzi Çakmak Mah. Gülistan Cad. No:11
Karatay/Konya
T: +90 332 503 11 44



+90 535 717 54 56