S

 σ

(1)

 σ

 \bigcirc

 \bigcirc

(1)

















Spring-Loaded Tine Plough



NPH Series



Mechanical and hydraulic adjustment of working-width



Optimal under-frame clearance



Uninterrupted work with rough conditions

Spring-Loaded Tine Plough

NPH	1	2	3	4	5	6	7	8
120x100 Frame								
Required Tractor Power (hp)	50-70	55-65	60-75	65-80	70-85	65-75	65-80	80-90
Weight (kg)	600	605	610	615	620	790	795	800
Number of Mouldboards	3	3	3	3	3	4	4	4
Mouldboard Size(Inch)	10	11	12	13	14	10	11	12
NPH	9	10	11	12	13	14	15	
120x100 Frame								
Required Tractor Power (hp)	80-95	85-95	70-90	70-100	80-95	80-100	100-120	
Weight (kg)	805	810	935	940	945	955	960	
Number of Mouldboards	4	4	5	5	5	5	5	
Mouldboard Size(Inch)	13	14	10	11	12	13	14	
NPH	16	17	18	19	20	21	22	23
140x120 Frame								
Required Tractor Power (hp)	80-90	85-95	80-95	85-100	100-120	100-120	100-125	130-160
Weight (kg)	840	880	1040	1070	1100	1220	1230	1300
Number of Mouldboards	4	4	5	5	5	6	6	6
Mouldboard Size(Inch)	12	14	12	13	14	12	13	14
		(Dptions	l	l	l		l
Grid Type Mouldboard								

Grid Type Mouldboard

Clod Breaker

+1 Mouldboard with Extra Frame

Product Description